

## Cetol® Marine Gloss

A clear gloss exterior wood coating based on a special alkyd resin specially developed as a topcoat over Cetol Marine in order to provide a durable finish for interior or exterior brightwork. Cetol Marine Gloss provides enhanced UV protection and weathering properties specifically designed for use in the Marine environment.

Highly transparent: ensures optimum visibility of the wood grain, enhancing the appearance of the wood.

Very good resistance to ultraviolet rays: lasting flexibility.

Weather resistant.

Water repellent.

Good gloss resistance.

Little dirt retention.

Marine brightwork (interior and exterior) and wood surfaces in a marine environment.

Note: Is not recommended to use Cetol Marine Gloss on its own. Cetol Marine should be used as first and second coat. Do not use Cetol Marine Gloss below the water line.

**Method** - Apply with a long haired, natural bristle brush.

**Temperature** - 10° C - 35° C (50° F - 95° F).

**Thinning** - Do not thin.

**Cleaning of equipment** - Mineral spirits, paint thinner, turpentine.

**Coverage** - Approximately 100 ft<sup>2</sup>/quart or 10m<sup>2</sup>/liter on a smooth wood per coat.

**Drying Time** - Dust dry after approximately 3 hours at 20° C (68° F). It is recoatable in 24 hours with a further coat of Cetol Marine Gloss.

During application, moisture content of the wood substrate should not exceed 18%.

## CHARACTERISTICS

## USE

## APPLICATION

## GENERAL REMARKS

**Viscosity** - 4.0 - 4.6 Poise at 23° C (73° F)  
**Density** - 0.91± 0.05 kg/dm<sup>3</sup>  
**Solids by Weight** - 53 - 55%  
**Solids by Volume** - 44 - 46%  
**Gloss Level** - High Gloss Finish  
**Flow** - Very Good  
**V.O.C.** - Less than 4.1 lbs/gal, 490 g/L - water free  
**Durability** - Good, provided maintenance of finish is followed regularly. Durability greatly depends on sufficient film thickness on initial application.  
Colorless

U.S. Quart

**Shelf Life** - Approximately 5 years in an unopened container.

**FLASH POINT:**

Approx. 40° C (105° F) (DIN 53213)

**WARNINGS:**

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep out of reach of children. Keep away from open flame or spark. Use only with adequate ventilation

**FIRST AID TREATMENT:**

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used, or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

## PROPERTIES

## COLOR RANGE

## PACKAGING

## STORAGE

## HEALTH & SAFETY DATA

## PRODUCT DISCLAIMER