

Cetol® Marine Light

Cetol Marine Light is a durable translucent satin protective wood finish. It was developed using a special alkyd resin and selected ultraviolet absorbing pigments, which results in superior weathering protection for teak and other commonly woods found on boats.

Highly transparent: ensures optimum visibility of the wood grain, enhancing the appearance of the wood.

Very good resistance to ultraviolet rays, lasting flexibility.

Microporous, allows the wood to breathe; withstands physical wear

Weather resistant.

Water repellent.

For use on teak and other woods commonly found on boats for interior or exterior.

Note: Cetol Marine may not be used below the water line.

Method - Apply with a long haired, natural bristle brush.

Temperature - 10° C - 35° C (50° F - 95° F).

Thinning - None; ready to use after stirring thoroughly.

Cleaning of equipment - Mineral spirits, paint thinner, turpentine.

Coverage - Approximately 85 ft²/quart or 8.7m²/liter on smooth wood per coat.

Drying Time - Dust dry after approximately 3-4 hours at 20° C (68° F) and 65% relative humidity. Recoat - not less than 24 hours between coats.

During application, moisture content of the wood substrate should not exceed 18%.

CHARACTERISTICS

USE

APPLICATION

GENERAL REMARKS

Viscosity - 1.2 - 1.6 Poise at 23° C (73.4° F)

Density - 0.91± 0.05 kg/dm³

Solids by Weight - 46.1 - 46.82%

Solids by Volume - 38.48 - 38.89%

Gloss Level - Satin Finish

Flow - Very Good

V.O.C.- Less than 4.1 lbs/gl, 490 g/L - water free

Durability - Good

Wood tone, Translucent color

U.S. Quart

Shelf Life - Approximately 5 years in an unopened container.

FLASH POINT:

Approx. 40° C (105° F) (DIN 53213)

WARNINGS:

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep out of reach of children. Keep away from open flame or spark. Use only with adequate ventilation

FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used, or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

PROPERTIES

COLOR RANGE

PACKAGING

STORAGE

HEALTH & SAFETY DATA

PRODUCT DISCLAIMER