

DURABILITY

Polybase Plus Basecoat

Polybase Plus is a catalyzed basecoat made from polyester and acrylic resins. Basecoat film has flexibility, adhesion and outstanding toughness. U-TECH Basecoat is extremely productive due to its fast flash-off, tack-off and re-coat times. Polybase Plus repairs without lifting swelling or wrinkling. Basecoat cross-linking provides extremely strong intra-coat adhesion with one coat application.



Product Features

- Easy application
- Hiding power
- Fast clearcoat time
- 3 day re-coat window
- Excellent repairability

Technical Data:

Mixing Ratio:	4:1:1	Potlife:	24 Hours
Substrates:	Existing Finishes	Flash Time:	5-7 Minutes
	U-TECH Primers	Tape Time:	30 Minutes @ 70° F
	U-TECH Surfacers and Sealers	To Clear:	20 Minutes @ 70° F
Coats:	1 - 2	Max Re-coat Time:	3 Days
Film build:	0.3 - 0.4 Mils per Coat	Ready-to-Spray VOC:	5.9 lb./gal.
Gun Setup:	HVLP Gravity (1.3 - 1.5) HVLP Siphon (1.8 - 2.2) Pressure Feed (1.0 - 1.2)		
Notes: Can be top-coated with any U-TECH Clearcoat.			



U-TECH

DRIVEN BY DURABILITY



9000-8016