

890 FLATTING AGENT

DESCRIPTION: 890 Flattening Agent is an additive that flattens topcoats and clearcoats. 890 Flattening Agent may be used in all U-Tech single stage colors and clearcoat systems.

PRODUCT & ADDITIVES:

PRODUCT: 890 Flattening Agent






BASIC RAW MATERIALS: Hydroxy acrylic resins:

SUITABLE SURFACES: 890 FLATTING AGENT MAY BE USED IN
 —All U-Tech Clearcoats prepared as recommended
 —All U-Tech single stage systems prepared as recommended

APPLICATION: —890 Flattening Agent can be used at many desired gloss levels in any U-Tech intermix single stage system and clearcoats. Below is a chart describing the gloss level in gu (gloss units). It is recommended to prepare a sprayout sample to determine the desired gloss.

MATTING POWER:

Gloss Level	% of 890 Flattening Agent added to color or clear
High (70-80 gu)	10%
Eggshell (50-60 gu)	20%
Semi gloss (40-50 gu)	30%
Matt (20-30 gu)	40%
Flat (10-20 gu)	50%

1.  Measurement by Weight
 100:30% = Semi gloss Finish
 Use the desired amount of 890 Flattening Agent to the clearcoat or intermix color
2.  Stir this mixture
3.  Mix the appropriate hardener and reducer for the desired intermix color or clearcoat.
4.  Use the U-Tech Measuring Stick.
5.  Please see the TDS of the product being used.



890 FLATTING AGENT

MIXING RATIO: Mix the single stage color or clearcoat by weight with the desired percentage of 890 Flattening Agent. After thorough stirring of this mixture, continue by adding the activator and reducers for the product being used.
Note: A spray out should be done first to determine desired gloss level.
For easy and accurate mixing, use the U-Tech measuring stick.

APPLICATION METHOD: The application method of the product will not change by adding 890 Flattening Agent.
Note: Wet flowing coats may increase the gloss level. The use of LV Flex Additive may also increase the gloss level.

CLEANING OF EQUIPMENT: Use Extra Strong Cleaning Solvent, or lacquer thinner.

STOCK KEEPING:

AVAILABILITY: 1 Quart

COLOR: White

CONTAINER SIZE: 890 Flattening Agent:

SHELF LIFE: Two years if stored in original package at room temperature

SAFETY ASPECTS:

READY TO SPRAY VOC: 890 Flattening Agent: 6.2 lb/gal 754 g/liter

NOTICE: Do not handle until the Material Safety Data Sheets have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all chemicals with which they come in contact. The manufacturer recommends the use of an air-supplied respirator when exposed to vapors or spray mist.