



R859 WAX AND GREASE REMOVER

DESCRIPTION: R859 Wax and Grease Remover is solvents especially formulated to remove grease and other contaminants from bare metal, existing finishes, etc.

BEFORE YOU CLEAN:

The purpose of cleaning and degreasing is to remove residual grease, oil, wax, silicones, oily road dirt, etc. If this is omitted, then residual contaminants may migrate into the fine scratches made during the sanding process. Possible silicone fish eyes and adhesion of the paint system applied to the contaminated may occur. Topcoat adhesion to the contaminated surface will be poor and the finish may blister or delaminate in a very short time.

1. Always first wash the car thoroughly with soap and water to remove as much contamination as possible and to eliminate as much dust and dirt as possible.
2. Always wear gloves when degreasing. This will accomplish two things:
 - a) Reduce the risk of solvent being absorbed into your hands.
 - b) Prevent salts and oils on your hands from contaminating the surface to be refinished.

APPLICATION:

R859 Wax and Grease Remover is a very good general purpose cleaner. It is suitable for cleaning and degreasing bare metal, existing finishes, primer surfacers, etc.




CLEANING TECHNIQUE:

When a repair is to be made or a finish is to be recoated, the first thing to do after soap and water washing the vehicle is to surface clean the body panel under treatment with R859. Wet a clean cloth with R859 Wax and Grease Remover and clean/degrease the surface under treatment. Immediately thereafter, wipe the surface dry with clean, dry cloths. Always use two cloths, as one cloth will merely shift rather than remove dirt and grease.

NOTE:

Replace cloths being used for degreasing and cleaning regularly by clean ones. Always place used degreasing rags in a sealed container that meets local requirements to avoid the risk of a spontaneous combustion fire.

R859 WAX AND GREASE REMOVER

- | | | | |
|-----|---|------------------------------------|--|
| 1. |  | Water | Wash down the vehicle with detergent and warm water. This will dissolve water-soluble contaminants. i.e., bird droppings, flies, tree sap, etc. |
| *2. |  | U-Tech R859 Wax and Grease Remover | Wash down area to be repaired with R859 Wax and Greaser Remover. This will remove any contaminant that cannot be removed with water. |
| *3. |  | | With a clean towel, dry off the degreaser and cleaner before it has time to evaporate.
—Always use one fresh towel for washing down and one fresh dry towel for wiping dry.
—Replace towels regularly. |

NOTE:

Never allow the surface cleaner to evaporate, the contaminate will remain. Wipe the surface dry with a clean towel before the degreaser is allowed to evaporate.

SANDED EXISTING FINISHES:

*Having sanded the existing finish, repeat Steps 2 and 3 one more time after sanding and prior to topcoating.

STOCK KEEPING:

CONTAINER SIZE:

1 gallon (3.785 lt)

SHELF LIFE:

Two years if stored in original container at room temperature.

SAFETY ASPECTS:

VOC:

U-Tech R859 Wax and Grease Remover 7.5 lb/gal 901 g/liter

NOTICE:

Do not handle until the Material Safety Data Sheets have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all chemicals with which they come in contact. The manufacturer recommends the use of an organic vapor respirator or air supplied respirator when exposed to vapors or spray mist.
